

STANDARD SPECIFICATION

- **Calculator** TBELTx with electronic volume/amount totalizers for every dispensing nozzle
- **Control valves** Electromagnetic proportional valve +24 V DC
- **Displays** LCD with LED backlight with 7 digits for amount, 6.5 digits for volume and 5 digits for unit price
- **Filter** Stainless steel, reusable, easy to clean
- **Fuel types** Petrol, Diesel, BioDiesel, Ethanol (E85), Kerosene and FAME
- **Hose management** Internal with free-hanging hoses for easy use with hose reach of 3.3 m
- **Hoses** DN 16, DN 21 or DN 25
- **Housing** Galvanized or powder-painted carbon steel
- **Meters** Pistons volume meter TATSUNO
- **Motors** Ex three-phase motor, 3 x 400 V / 50 Hz, 0.75 kW, 1,395 rpm
- **Nozzles** Wide range of nozzles
- **Pulsers** Magnetic or optoelectronic pulse transmitter TATSUNO with electronic volume correction
- **Suction pumps** Monoblock TATSUNO with gear pump, air separator and air sensor

OPTIONS

- Automatic temperature volume correction (ATC)
- Breakaway couplings
- Customizable colours
- Electro-mechanical totalizers
- Flexible pipe connection
- Foundation frame
- Housing - stainless steel and/or flame resistant fibreglass
- Infra-red remote controller
- Main safety switch (TOTAL STOP)
- Payment terminal – integrated solution for wide range of terminals
- PDEX calculators with electronic volume/amount totalizers for every dispensing nozzle
- Proportional graphics display with customer text messages
- Pulse interface
- Remote version – ready for connection with submersible pump installed inside the tank
- Satellite hose & nozzle
- Sight glasses
- Single phase power supply
- Sound module
- Ultra high speed flow rate 160 L/min with LOBE flow meter
- Vapour recovery system
- Volume and amount preset function via push buttons
- Wide range of data line communication protocol converters
- 40 / 80 L / min flow rate switch

Product images are for illustrative purposes only.

 **TATSUNO EUROPE a.s.**

Pražská 68, 678 01 Blansko, Czech Republic
P: +420 516 428 411 / F: +420 516 428 410 / E: info@tatsuno-europe.com
www.tatsuno-europe.com

TATSUNO

BMP 4000.OT TALL ELECTRONIC FUEL DISPENSERS



OCEAN Line **CUBE**



OCEAN Line **FIN**



BMP 4000.OT TALL ELECTRONIC FUEL DISPENSERS

The fuel dispensers TATSUNO of series OCEAN TALL serve for dispensing of liquid oil products into road vehicles on retail and commercial outlets.

OCEAN TALL are progressive single or double sided fuel dispensers with one to ten hoses (max. five hoses on each fuel dispenser side) for dispensing one to five products. The fuel dispensers are equipped by the highest quality Japanese hydraulic system TATSUNO and by a reliable electronic calculator.

A simple and attractive design with durable materials in addition to composite plastic nozzle boots and countless design configurations lasts longer and offers certain benefit to its users.



- 
new original design
- 
automatic temperature volume correction
- 
hydraulics Tatsuno (Japan)
- 
graphics displays
- 
effective vapour recovery


DESIGN MODIFICATIONS



OCEAN Line **CUBE**



OCEAN Line **FIN**



SINGLE-SIDED DISPENSERS OCEAN BMP4000.OT TALL

Product	Type	Hoses/ Performance
1	BMP4011.OTL(R)	1 × 40 L / min
2	BMP4022.OTL(R)	2 × 40 L / min
3	BMP4033.OTL(R)	3 × 40 L / min
4	BMP4044.OTL(R)	4 × 40 L / min
5	BMP4055.OTL(R)	5 × 40 L / min

DOUBLE-SIDED DISPENSERS OCEAN BMP4000.OT TALL

Product	Type	Hoses/ Performance
1	BMP4012.OTD	2 × 40 L / min
2	BMP4024.OTD	4 × 40 L / min
3	BMP4036.OTD	6 × 40 L / min
4	BMP4048.OTD	8 × 40 L / min
5	BMP40510.OTD	10 × 40 L / min

TECHNICAL & ENVIRONMENTAL SPECIFICATION

Flow rates	Standard speed flow rate: 40 L / min	High speed flow rate (H): 80 L / min	Ultra high speed flow rate (UH): 130 L / min
Accuracy	± 0.25 % with minimum dispensed volume 2 L (/ H – 5 L, / UH – 10 L)		
Power supply	230/400 V AC, three phase 50 Hz		
Ambient temperature	–25 °C to +55 °C (–40 °C to +55 °C with additional heating)		
Temperature of fluid	–25 °C to + 50 °C		
Relative humidity	5 % to 95 %		

